

Preferred Pack[®]

Fully Automatic Combination L' Sealer and Tunnels



"APA"
Automatic Product
Adjustment



Delta PLC with 12 program memory and self diagnostics

PP-5300C & PP-5600C Combinations
Compact - Portable - Affordable



Optional 3' or 6' flighted or belted infeed conveyor - increases speed

The new PP-5300C & PP-5600C are the only automated L' Sealer and Tunnels to feature "APA" Automatic Product Adjustment, operator simply selects desired program from the one touch control panel and the machine will automatically adjust the infeed conveyor and inverting triangle to package size in less than 15 seconds. Imagine no more fussing with crank handles or guessing the proper package size.


Automatic L' Sealer Features

- "APA" - Automatic Product Adjustment
- Speeds up to **40 PPM**
- Vertical seal head design
- Fast product changeovers
- **"Single Piece"** hot knife seal blade
- 7" Color Touch screen control panel
- Variable speed drive 0-110 FPM
- **Delta PLC** with 12 program memory
- Motorized adjustment of seal head
- Pin wheel hole punch
- Front load film cradle
- Seal area 19"L x 16"W
- **Self diagnostics** for safety sensors, low voltage, broken scrap wind etc.
- Emergency stop switch
- Self Contained scrap removal system with built in alarm when full

Shrink Tunnel Features

- Dual lighted viewing window
- Chamber size 18"W x 7"H x 38"L
- **Energy efficient**
- 1HP blower motor
- Fully re-circulating air chamber
- Live roller rod conveyor
- **Digital temperature** controller programmable 0 to 400 degrees
- 10 KW heater bank
- Tunnel adjusts side to side, will center package into tunnel
- **Variable speed drive 0-110 FPM**
- Solid state digital temperature controller
- Automatic cool down and shut off
- **CE Approved safety system**, Exceeds OSHA safety standards


Fully Automatic Combination L' Sealer and Tunnels



Re-circulating air chamber with live roller conveyor




Easy front load film cradle with pin wheel hole punch



Motorized inverting triangle for pkg height adjustment



Easy access control panel



Vertical seal head with one piece seal knife and blade

Model	PP-5300C	PP-5600C
Seal Area	19"L x 16"W x 5"H	25"L x 19"W x 7"H
Machine speed	Up to 40 PPM	Up to 40 PPM
Electrical	220V, 1 Phase, 50 AMP	220V, 1 Phase, 50 AMP
Air	1CFM @ 80 PSI	1CFM @ 80 PSI
Minimum pkg size	2.5" x 2.5" x 1/8"	2.5" x 2.5" x 1/8"
Maximum pkg size	19"L x 16"W x 5"H	25"L x 19"W x 7"H
Maximum Film width	24"	24"
Tunnel dimensions	40" L x 18"W x 8"H	40" L x 18"W x 8"H
Created dimensions	118"L x 64"W x 73"H	
Shipping weight	2,500 lbs	
Warranty	1yr on parts - 2 yrs on seal head	

Available Options
<ul style="list-style-type: none"> • Pneumatic hole punch • 3' flighted infeed • 6' flighted infeed • Belted conveyors • Flight bar conveyors for multi-packs • Closing conveyor • Print registration

PP-5300C & PP-5600C Dimensions

